

# HEAVY DUTY HIGH INTENSITY HEATER



**SUPERIOR**  
RADIANT PRODUCTS

**RIGID  
HEAVY DUTY  
CONSTRUCTION**

## **SERIES S - STANDARD EFFICIENCY HIGH INTENSITY HEATER**

**Directed, cost-effective heat  
for cold spots in industrial and  
commercial applications**

- Entire construction is non-corrosive aluminized steel
- Low profile requires less space
- Reliable direct spark or millivolt ignition
- Unique pattern high output ceramics
- Performance enhancing screens
- Modular head construction
- Rates 30,000 to 160,000 BTUH
- NG or LPG





Model S



Maximized radiant efficiency  
with high-polished aluminum  
reflector

**SUPERIOR TECHNOLOGY SUPERIOR PERFORMANCE**  
**WWW.SUPERIORRADIANT.COM**

# SERIES S – HEAVY DUTY HIGH INTENSITY HEATER

Heater	Part No.	BTU/HR		Radiating Surface (Sq. In.)	Dimensions			Shipping Weight (lbs.)
		Natural Gas	LPG		Height	Length	Width	
	SD03N*	33,000	–	90	9.2"	16.3"	24.4"	36
	SD03P*	–	30,000					
	SD06N*	66,000	–	180	9.2"	23.1"	24.4"	44
	SD06P*	–	60,000					
	SD09N*	99,000	–	270	9.2"	30.0"	24.4"	56
	SD09P*	–	90,000					
	SD12N*	132,000	–	360	9.2"	36.9"	24.4"	64
	SD12P*	–	120,000					
	SD16N*	160,000	–					

\*Substitute "M" for "D" for Millivolt

General Specifications		Inlet Pressure			Accessories Available
Power Supply	24v	–	Natural Gas	Propane	<ul style="list-style-type: none"> <li>• Chain Kits</li> <li>• Thermostats</li> <li>• Transformers</li> <li>• Gas Flex Connectors</li> <li>• Gas Shut Off Valves</li> </ul>
Control	Direct Spark or Millivolt Ignition	Minimum	6.5" WC	11" WC	
Gas Supply	1/2" NPT	Maximum	1/2 psig.	1/2 psig.	



**SUPERIOR**  
RADIANT PRODUCTS



Superior Radiant Products Ltd.  
563 Barton Street  
Stoney Creek, ON L8E 5S1 Canada

Superior Radiant Products Inc.  
100 - 980 Cobb Place Blvd. NW  
Kennesaw, GA 30144-6801 USA

1 800 527 HEAT(4328) | tel 1 905 664 8274 | fax 1 905 664 8846  
sales@superiorradiant.com | www.superiorradiant.com

**SUPERIOR TECHNOLOGY SUPERIOR PERFORMANCE**

DISTRIBUTOR