			TECHNICAL S	SPECIFIC	ATIONS
			VOLTS	120	V
			AMPS	12.5	5 A
			WATTS	150	0 watts
			HEATER H	IIGH 150	0 watts
			L	.OW 750	watts
			NO HEATER	31 \	watts Max.
			LAMPS T	YPE LEC)
			TOTAL WA	TTS 28 v	watts
			ROTOR MOTOR	1 at	t 2.9 watts
		3	HEIGHT,WIDTH,DEPTH	15 🖁	"×60 ¹ / ₄ "×5 ¹ / ₂ "
		$\frac{3}{4}$ "	GLASS VIEWING OPEN	IING 58 ½	<u>1</u> ⁻ ×13 <u>1</u> ⁻
	[SURROUND SIZE	62 1/4	¦ "×16 ⁷ / ₈ "
$\begin{array}{c c c c c c c c c c c c c c c c c c c $			SHIPPING SIZE	69 2	$\frac{1}{2}$ " × 10 $\frac{7}{8}$ "× 21 $\frac{5}{8}$ "
			SHIPPING WEIGHT	101	.20 LBS
		=	ι		
			GLASS FR	ONT Incl	uded
	•		PLUG LOCATION	Left	Side
		•	CORD LENGTH	70 7	⅓ " <l<95 th="" ½"<=""></l<95>
$62\frac{1}{4}$ "	$5\frac{1}{2}$ "	I	APPROX. HEATING AR	EA 400) sq ft
$6 0 \frac{1}{4}$ "					
<					
		Λ	nanti		
		K.	nonti	i.	
				\sim	
		MODEL			
	RIES	MODEL			REV.
	BESPOKE	SYM-60			1
	SCALE	DATE:	22/6/2020	SHE	ET 1 OF 1